

pewag winner profilift lifting points

Lifting and lashing





dlhonline.co.uk 0161 223 1990 Content

Screwable and weldable lifting points from pewag

pewag winner profilift lifting points stand for best quality and advanced innovation that set new standards within the chain industry in terms of lifting and moving of loads. As an ideal addition to the successful pewag winner lifting chains assortment the pewag winner profilift lifting points ensure a high degree of safety, user friendliness and compatibility.

Content	3
pewag group	
Welcome to the pewag group History, Quality management Business areas, Environment Production and sales locations	4–5 6 7 8
peTAG solution	
peTAG solution	10–11
Screwable lifting points	
Screwable lifting points	12–27
Weldable lifting points	
Weldable lifting points	28–31
Spare parts	
Spare parts	32-35
User manual	
User manual	36–39

Technical changes and misprints are subject to alteration.

dlhonline.co.uk 0161 223 1990 Welcome to the pewag group

We are an internationally operating group of companies. Our track record goes back to the year 1479.

Mission Statement pewag group's Mission Statement expresses the goals of our actions as follows:

With our joy for innovation, we ensure that all products of the pewag group are the best in the respective markets, both now and in the future. The high quality of our products and services as well as our employees' passionate dedication are the foundation to our pursuit of outstanding services and complete customer satisfaction.

Principles of pewag group

Leading in Quality

The values of our premium product brands are demonstrated by our first class quality and innovations and are communicated consistently and coherently.

We anticipate market demands and changes in the environment and adapt our strategies, organizations and actions accordingly to satisfy our customers' needs through providing the best value for the money; timely delivery; efficient and obliging service.

Leading in Responsibility

We commit ourselves to careful treatment of the environment, by reducing the use of energy and raw materials, ensuring the longevity of our products and making them recyclable.

We value an open, honest and team-oriented work-style, which is based on transparent communication honoring ideas, opinions and experience of our employees as valuable inputs for our decision making process.

We strive for stable and fair partnerships with our employees, customers, suppliers and other business partners and take social aspects into consideration when making business decisions.

Leading in Technology

We secure our technological leadership through highest product quality, constant improvements and innovations of products, as well as manufacturing processes.

We are dedicated to keep on top of product technology. This ensures that our customers always have the best solutions available and that we expand and protect our market position.

Leading in Economics

In all our processes we use due diligent business practices and efficiency and strive to improve these continuously.

In the long-term, we will continuously increase our economic performance to raise corporate value, achieve sustained growth and thus secure a successful future of the organization.



pewag

We are a modern group of companies which looks back to a tradition and experience of more than 500 years. Since our founding years, a lot has changed, but the values that made our success possible from the beginning remain.

pewag group – Innovation. Quality. Partnership.

001110

dlhonline.co.uk 0161 223 1990 History

of the pewag group

Advantage through tradition

The history of pewag group goes back to the 15th century and therefore makes us the oldest chain manufacturer worldwide. With our experience we are ready for the future.

Timetable of important events

1479 First documented references of a forging plant in Brückl

- 1787 Foundation of a chain forge in Kapfenberg
- 1803 Foundation of a chain forge in Graz
- 1836 Establishment of an iron casting plant in Brückl
- **1912** Production of the first snow chain in the world
- **1923** Merger of plants in Graz and Kapfenberg Creation of the name "pewag"
- 1972 Foundation of a sales company in Germany
- 1975 Foundation of a sales company in the USA
- **1993** Foundation of pewag austria GmbH
- 1994 Foundation of the first subsidiary in Czech Republic
- 1999 Acquisition of the Weissenfels Group
- 2003 Separation from the Weissenfels Group
- 2005 Reorganization into 2 groups: Schneeketten Beteiligungs AG Group – Snow Chains pewag austria GmbH Group – Technical Chains
- 2009 Acquisition of Chaineries Limousines S.A.S.2012 Foundation of the first manufacturing company in the USA
- **2013** Foundation of various international sales companies



Lithography forging plant Brückl 1855



Anchor chain forge 1878



Chain forgers 1956

Our main goal is customer satisfaction.

management

Quality

In this instance, quality means that only those products and services are developed, manufactured and delivered which completely and without compromise satisfy the customer. The pewag group's quality policy, is underlined by the following basic principle: **"we supply high-end products and services to our customers that conform to the technical standards and requirements**", can be summarised in the subsequent four points.

Market-oriented Quality

In order to maintain and to widen the competitive position of the pewag group, the quality of finished goods and services must be consistent with the specifications of the customer and also with their expectations of a technological leader. No product should ever pose a danger to people or the environment.

Economic Quality

As a profit-oriented company, quality is achieved by taking into consideration the material, personnel and financial resources; this means that we establish an appropriate best price/performance ratio for the customer within the acknowledged framework.

Quality Responsibility

Stringent demands are placed on all employees to ensure high standards of quality. No matter what hierarchical level, all managers are in charge of managing quality. Every employee within the pewag group should be educated, motivated and instructed by the management team. It is important for promoting high quality awareness that the education and training of employees is at the forefront, as each employee is responsible for the quality of his/her own work.

For each of our employees, the statement "QUALITY STARTS WITH ME" must be true!

Process-oriented Quality

The close interaction between sales, product development, production and customer service is regulated within the individual companies by fixed processes and activities, as well as responsibilities with the aim to reach and maintain the defined quality standards.



pewag

Business areas

Environment we take responsibility

Working with pewag products

The pewag group has a substantial and diverse spectrum of products and services.

Our range of products varies from traction chains for tires (snow chains for passenger cars, trucks and special-purpose vehicles, tire protection chains for mining vehicles) over different industrial chains to products for the do-it-yourself sector (light chains, belts, etc.)



Segment A Snow and forestry chains



Segment B Hoist and conveyor chains



Segment C Do-it-yourself



Segment F Lifting and lashing chains and accessories



Segment D Engineering



Segment G Tire protection chains

Ecological awareness in all areas



Our company's manufacturing location in Kapfenberg, Austria, has been used for iron and steel production for over 270 years. A second facility located in Brückl, Austria, was first documented in records dating back to 1479. Based on this long

manufacturing tradition, we take serious responsibility for our products, employees and the environment at all our international locations. Hence, one of our major concerns is to improve energy efficiency and, in doing so, to minimise energy consumption over a long period of time with the development of new production technologies. An important goal is to increase energy efficiency and consequently lower energy demand. Consequently, we develop our products to achieve longer product life-cycles and lower weight but simultaneously, increasing their working load capacities and the safety for our customers. We are committed to upholding all relevant energy and environmental standards by setting clearly defined goals and continually improving our performance. To achieve this goal, we use modern manufacturing technologies. An important step is to provide the necessary resources and to include our employees in the process. We are convinced that well-informed and motivated employees can actively participate in environmental conservation.

Wherever we are unable to avoid an environmental impact, we have set ourselves the goal to continually reduce our energy consumption, waste and environmentally harmful emissions. When purchasing new equipment, we strive to find the best and most efficient technical solution possible. It is important for us to promote the purchase of energy efficient products and services.

Our process-oriented management system regulates the documentation concerning all environmental relevant procedures. It also encompasses preventative measures for possible failures, as well as behavioural instructions for regular and/or extraordinary operational procedures. By systematically monitoring and assessing our environmental activities, we are quickly able to resolve deviances and to take corrective action. This process extends throughout the whole organisation to optimise all business processes. We strive to engage in an open dialogue with our customers, neighbours and authorities to inform them of our energy and environmental engagements.

Through specific communication we want to inform our customers about the environmental aspects of our products - specifically inform them about the longevity of our products. Through meaningful communication, we strive to motivate our suppliers and customers to think - in turn - about their environmental footprint and to put into practice similar environmental standards in their businesses

Customer proximity

International presence

In the ambitious five-hundred year history pewag has evolved from a small and modest company to a global organization with several subgroups.

With 11 production and 31 sales and other locations on the continents of Europe, America, Africa and Australia pewag documented its claim as the world's number one chain manufacturer.

In addition to the numerous locations pewag as an international company relies on his capillary, strong, and professional partner network. These collaborations provide optimal customer service in currently more than 100 countries around the world.

Production and sales locations

Europe

Austria	pewag austria GmbH, Graz pewag austria GmbH, Kapfenberg pewag Schneeketten GmbH & Co KG, Graz pewag Schneeketten GmbH & Co KG, Brückl pewag engineering GmbH, Kapfenberg pewag austria Vertriebsgesellschaft mbH, Wien pewag Ketten GmbH, Klagenfurt pewag International GmbH, Klagenfurt
Germany	pewag Deutschland GmbH, Unna pewag Schneeketten Deutschland GmbH, Unna
France	pewag France SAS, Èchirolles/Grenoble Chaineries Limousines SAS, Bellac Chaineries Limousines SAS, Limoges
Italy	pewag italia srl, Andrian Acciaierie Valcanale Srl, Tarvisio
The Netherlands	pewag nederland BV, Hillegom APEX International BV, Hillegom
Poland	pewag polska Sp z o.o., Buczkowice
Portugal	pewag Portugal, Santo Antão do Tojal
Russia	OOO "PEWAG", Moscow OOO "pewag russia", Moscow
Kazakhstan	Representative office of pewag international GmbH, Almaty
Croatia	pewag croatia doo, Zagreb
Sweden	pewag sweden AB, Emmaboda

Europe

<u>.</u>	
Slovakia	pewag slovakia sro, Nitra
Czech Republic	pewag Snow Chains s.r.o., Česká Třebová pewag sro, Vamberk KOMAP Dědov sro, Dědov KOMAP Dědov sro, Chrudim
Ukraine	TOV pewag Ukraine, Lviv
North Ameri	ca
USA	pewag Inc, Bolingbrook, Illinois pewag Inc, Rocklin, California pewag Traction Chain Inc, Pueblo
Mexico	pewag Mexico S.A. de C.V., Mexico
South Ameri	ca
South Ameri Brazil	ca pewag Brasil Comércio de Correntes Ltda., São Paulo
South Ameri Brazil Africa	ca pewag Brasil Comércio de Correntes Ltda., São Paulo
South Ameri Brazil Africa South Africa	ca pewag Brasil Comércio de Correntes Ltda., São Paulo pewag chain south africa (pty) Itd., Rivonia HMV Engineering (Pty) Ltd, Houghton Johannesburg
South Ameri Brazil Africa South Africa Australia	ca pewag Brasil Comércio de Correntes Ltda., São Paulo pewag chain south africa (pty) Itd., Rivonia HMV Engineering (Pty) Ltd, Houghton Johannesburg



pewag

pewag group presents itself on the internet. More ... www.pewag-group.com www.pewag.com

pewag group – Innovation. Quality. Partnership.





10

dlhonline coluk 0161 223 1990 pewag





Content

12

Screwable lifting points

14–15
16–17
18
19
20–21

dlhonline.co.uk 0161 223 1990

PLBW pewag winner profilift beta	22–23
PLDW pewag winner profilift delta	24–25
AOR lashing point	26
RGS alloy steel eyebolt	27



dlhonline.co.uk 0161 223 1990 **Pewag**

Screwable lifting points

Product Overview



Safe. Innovative. pewag.

Competent safety in case of lifting and lashing for the operating staff and goods

The premium Austrian chain manufacturer pewag - standing for innovation, quality and safety - offers in the area of lifting points high quality products that set new standards within the chain industry in terms of lifting and moving of loads. pewag winner profilift lifting points are perfectly suited as an addition to the world wide successful pewag winner lifting chains. pewag places great emphasis on continuous improvements and innovations in the field of lifting point, thus keeping one step ahead of the market at all times. Simultaneously we are working on the further extension of the lifting points assortment, whereas safety, user friendliness and comptability are placed at the central point. Each pewag winner lifting point is marked with an individual serial number and convinces with an innovative design.

pewag winner profilift lifting points correspond to the Machine-Directive (MRL) 2006/42/EG respectively Machine-Safetyprescriptions (MSV) 2010 as well as EN 1677-1 and technical specifications. The pewag winner profilift lifting points are produced in our ISO 9001 and 14001 certified plants and guarantee a 4respectively 5-fold safety and a maximum dynamic load of min. 20.000 load cycles, tested at 1,5-fold working load limit.

The table with the working load limit - depending on the type of application as lifting gear, number of legs and angle of inclination - is a part of the detailed user manual corresponding to the Machine-Safety-prescriptions 2010 and Machine-Directive and is packed together with each lifting point.

Stamping of the serial number

Testing in pewag laboratory

Screwable lifting points **Overview**

PLGW pewag winner profilift gamma	Code	Thread	Load capacity
supreme and basic		[mm]	[kg]
(part)	PLGW 0,3 t	M8 x 1,25	300
	PLGW 0,5 t	M10 x 1,5	500
	PLGW 0,7 t	M12 x 1,75	700
	PLGW 1,5 t	M16 x 2	1.500
	PLGW 2 t	M20 x 2,5	2.000
	PLGW 2,3 t	M20 x 2,5	2.300
	PLGW 3 t	M24 x 3	3.000
	PLGW 3,2 t	M24 x 3	3.200
	PLGW 4 t	M30 x 3,5	4.000
	PLGW 4,9 t	M30 x 3,5	4.900
	PLGW 7 t	M36 x 4	7.000
	PLGW 9 t	M42 x 4,5	9.000
	PLGW 12 t	M48 x 5	12.000

PLGW-SN pewag winner profilift gamma	Code	Thread	Load capacity
supreme		[mm]	[kg]
	PLGW-SN 0,7 t	M12 x 1,75	700
\square	PLGW-SN 1,5 t	M16 x 2	1.500
	PLGW-SN 2,3 t	M20 x 2,5	2.300
	PLGW-SN 3,5 t	M24 x 3	3.500

Mounting Video PLGW

PLAW pewag winner profilift alpha	Code	Thread [mm]	Load capacity [kg]
	PLAW 0,3 t	M8 x 1,25	300
	PLAW 0,63 t	M10 x 1,5	630
	PLAW 1 t	M12 x 1,75	1.000
	PLAW 1,5 t	M16 x 2	1.500
	PLAW 2,5 t	M20 x 2,5	2.500
	PLAW 4 t	M24 x 3	4.000
	PLAW 6 t	M30 x 3,5	6.000
	PLAW 7 t *	M36 x 4	7.000
	PLAW 8 t	M36 x 4	8.000
	PLAW 10 t	M42 x 4,5	10.000
	PLAW 15 t	M42 x 4,5	15.000
	PLAW 20 t	M48 x 5	20.000

* Special models available on request!

PLBW pewag winner profilift beta	Code	Thread [mm]	Load capacity [kg]
	PLBW 0,3 t	M8 x 1,25	300
	PLBW 0,6 t	M10 x 1,5	600
	PLBW 1 t	M12 x 1,75	1.000
	PLBW 1,3 t	M14 x 2	1.300
	PLBW 1,6 t	M16 x 2	1.600
	PLBW 2 t	M18 x 2,5	2.000
	PLBW 2,5 t	M20 x 2,5	2.500
, U	PLBW 3 t	M22 x 2,5	3.000
	PLBW 4 t	M24 x 3	4.000
	PLBW 5 t	M27 x 3	5.000
	PLBW 6,3 t	M30 x 3,5	6.300
	PLBW 8 t	M33 x 3,5	8.000
	PLBW 10 t	M36 x 4	10.000
	PLBW 12,5 t	M42 x 4,5	12.500
	PLBW 15 t	M48 x 5	15.000

Code	Thread [mm]	Load capacity [kg]
PLDW 0,3 t	M8 x 1,25	300
PLDW 0,5 t	M10 x 1,5	500
PLDW 0,7 t	M12 x 1,75	700
PLDW 1 t	M14 x 2	1.000
PLDW 1,5 t	M16 x 2	1.500
PLDW 2,5 t	M20 x 2,5	2.500
PLDW 4 t	M24 x 3	4.000
PLDW 6 t	M30 x 3,5	6.000
PLDW 8 t	M36 x 4	8.000
PLDW 10 t	M42 x 4,5	10.000
PLDW 12,5 t	M48 x 5	12.500

AOR Lashing point

Code	Thread [mm]	Load capacity [kg]
AOR 10	M16 x 2	3.150
AOR 13	M20 x 2,5	5.300
AOR 16	M30 x 3,5	8.000
AOR 22	M36 x 4	15.000
AOR 26	M42 x 4,5	21.200
AOR 28	M45 x 4,5	25.000
AOR 32	M56 x 5,5	31.500
AOR 34	M56 x 5,5	36.000

.

RGS Alloy steel eyebol

	AOR 34	M56 x 5,5	36.000
lt	Code	Thread [mm]	Load capacity [kg]
	RGS 8	M8 x 1,25	400
	RGS 10	M10 x 1,5	700
	RGS 12	M12 x 1,75	1.000
	RGS 14	M14 x 2	1.200
	RGS 16	M16 x 2	1.500
	RGS 20	M20 x 2,5	2.500
	RGS 24	M24 x 3	4.000

15

PLGW pewag winner profilift gamma

pewag winner profilift gamma supreme – tighten by hand, then align in the load direction, a lifting point that has been developed and produced with the new standards in mind. The patented system has proven itself from the beginning.

It is 360° rotatable, contains a patented and interchangeable special screw, which is 100% crack-tested as well as covered with a chrome VI-free finish-protection against corrosion and marked with WLL and thread size.

Tool-free assembly and disassembly

The latch in pos.1 does not have any contact with the screw (picture 1).

- The latch is kept in position with a patented spring
- Eye bolt is rotatable

The latch in pos. 2 has contact with the screw (picture 2).

- · The latch is kept in position with a patented spring
- Eye bolt is not rotatable i.e. the fastening torque is transmitted to the screw and thus the eye bolt can be (re)assembled

A considerably simplified alternative is the pewag PLGW pewag winner profilift gamma basic. With the same benefits as the pewag PLGW supreme in terms of measurement, carrying capacity and application, the pewag PLGW basic differs solely in the assembly: mounting and removing requires the use of a hexagon Allen wrench.

PLGW Basic - screw on with tools

PLGW Supreme – tool-free assembling

Picture 1 PLGW Supreme rotatable

Picture 2 PLGW Supreme dis-/assembly

Code	Thread [mm]	Fastening torque [Nm]	Load cap [kg]	acity								
PLGW 0,3 t	M8		800	300	1.600	600	400	300	600	400	300	300
PLGW 0,5 t	M10		1.100	500	2.200	1.000	700	500	1.000	700	500	500
PLGW 0,7 t	M12		2.000	700	4.000	1.400	1.000	700	1.400	1.000	700	700
PLGW 1,5 t	M16	Osa ha tishtara d	4.000	1.500	8.000	3.000	2.100	1.500	3.000	2.200	1.500	1.500
PLGW 2 t	M20	Can be tightened	5.000	2.000	10.000	4.000	2.800	2.000	4.200	3.000	2.000	2.000
PLGW 2,3 t*	M20	mandany	5.000	2.300	10.000	4.600	3.200	2.300	4.800	3.400	2.300	2.300
PLGW 3 t	M24		6.500	3.000	13.000	6.000	4.200	3.000	6.200	4.500	3.000	3.000
PLGW 3,2 t*	M24		6.500	3.200	13.000	6.400	4.500	3.200	6.700	4.800	3.200	3.200
PLGW 4 t	M30		12.000	4.000	24.000	8.000	5.600	4.000	8.200	6.000	4.000	4.000
PLGW 4,9 t*	M30		12.000	4.900	24.000	9.800	6.900	4.900	10.300	7.300	4.900	4.900
PLGW 7 t	M36		15.000	7.000	30.000	14.000	9.800	7.000	14.700	10.500	7.000	7.000
PLGW 9 t	M42		22.000	9.000	44.000	18.000	12.600	9.000	18.900	13.500	9.000	9.000
PLGW 12 t	M48		30.000	12.000	60.000	24.000	16.800	12.000	25.000	18.000	12.000	12.000
* Higher carrying	capacity, soon	only available in this des	sian!									

Code	Thread [inch]	Fastening torque [Ib/ft]	Load cap [lbs]	acity								
PLGW U 3/8	3/8"-16		2.400	1100	4.800	2.200	1.500	1.100	2.200	1.500	1.100	1.100
PLGW U 1/2	1/2"-13		4.400	1500	8.800	3.000	2.200	1.500	3.000	2.200	1.500	1.500
PLGW U 5/8	5/8"-11		8.800	3300	17.600	6.600	4.600	3.300	6.600	4.800	3.300	3.300
PLGW U 3/4	3/4"-10	Can be tightened	9.900	4.400	19.800	8.800	6.100	4.400	9.200	6.600	4.400	4.400
PLGW U 1	1"-8	manually	11.000	6.600	22.000	13.200	9.200	6.600	13.600	9.900	6.600	6.600
PLGW U 1 1/4	1 1/4"-7		22.000	8.800	44.000	17.600	12.300	8.800	18.000	13.200	8.800	8.800
PLGW U 1 1/2	1 1/2"-6		33.000	15.400	66.000	30.800	21.500	15.400	32.300	23.100	15.400	15.400
PLGW U 1 3/4	1 3/4"-5		40.000	19.800	80.000	39.600	27.700	19.800	41.500	29.700	19.800	19.800
										A.U. U. 0		

Safety factor 4

Screwable lifting points

dlhonline.co.uk 0161 223 1990 pewag

Permissible usage

Load capacity acc. to the inspection certificate table of WLL in the shown directions of pull (see picture 3).

- Adjust the lifting point in the permitted load direction before loading
- · Loadable with a 4-fold safety under break in all directions

Non permissible usage

Make sure when choosing the assembly that improper loading can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area (see picture 4)
- Loading ring rests against edges or loads

For more details please reference our user manual.

To calculate the necessary thread length (L):

 $\mathsf{L}=\mathsf{H}+\mathsf{S}+\mathsf{K}+\mathsf{X}$

- H = Material height
- S = Thickness of the washer
- K = Height of the nut (depending on the thread size of the screw) X = Excess length of the screw (twofold pitch of the screw) L max. = n max.

In case of requesting a lifting point with a special thread length, please mention the requested thread length "L".

pewag provides, along with the standard and maximum thread lengths, specially customised thread lengths.

Supplied customised and maxium thread lengths include a washer and a crack-tested, corrosion-proofed screw nut.

Each lifting point is marked with an individual serial number.

Picture 3

Picture 4

Code	Thread [mm]	Load capacity [kg]	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	Ø f [mm]	n [mm]	n max. [mm]	(mm]	Weight [kg/pc.]
PLGW 0,3 t	M8	300	25	45	10	27	53	35	15	90	6	0,17
PLGW 0,5 t	M10	500	25	45	10	27	53	35	15	160	6	0,18
PLGW 0,7 t	M12	700	30	55	12	32	63	43	20	160	8	0,29
PLGW 1,5 t	M16	1.500	35	64	14	36	70	50	25	160	10	0,45
PLGW 2 t (2,3 t)	M20	2.000	40	69	16	41	78	54	30	160	12	0,58
PLGW 3 t (3,2 t)	M24	3.000	50	86	18	50	97	69	35	-	14	1,10
PLGW 4 t (4,9 t)	M30	4.000	60	110	25	60	114	90	45	-	17	2,20
PLGW 7 t	M36	7.000	70	132	31	70	136	108	55	-	19	3,90
PLGW 9 t	M42	9.000	80	152	36	72	153	126	65	-	22	5,80
PLGW 12 t	M48	12.000	95	179	42	88	179	148	75	-	24	8,90
Code	Thread [inch]	Load capacity [lbs]	a [inch]	b [inch]	c [inch]	d [inch]	e [inch]	Ø f [inch]	n [inch]	n max. [inch]	(inch]	Weight [lbs/pc.]
PLGW U 3/8	3/8"-16	1.100	0,98	1,77	0,39	1,04	2,09	1,38	0,60	-	1/4"	0,40
PLGW U 1/2	1/2"-13	1.500	1,18	2,17	0,47	1,26	2,48	1,69	0,80	-	5/16"	0,64
PLGW U 5/8	5/8"-11	3.300	1,38	2,52	0,55	1,40	2,76	1,97	1,00	-	3/8"	0,99
PLGW U 3/4	3/4"-10	4.400	1,57	2,72	0,63	1,59	3,07	2,13	1,20	-	1/2"	1,28
PLGW U 1	1"-8	6.600	1,97	3,39	0,71	1,97	3,82	2,72	1,40	-	9/16"	2,43
PLGW U 1 1/4	1 1/4"-7	8.800	2,36	4,33	0,98	2,36	4,49	3,54	1,80	-	5/8"	4,85
PLGW U 1 1/2	1 1/2"-6	15.400	2,76	5,20	1,22	2,76	5,35	4,25	2,20	-	7/8"	8,60
PLGW U 1 3/4	1 3/4"-5	19.800	3,15	5,98	1,42	2,83	6,02	4,96	2,60	-	1"	12,80

PLGW-SN pewag winner profilift gamma supreme

Screwable lifting points

pewag's new PLGW-SN pewag winner profilift gamma supreme lifting eye nut is the logical continuance to the successful PLGW product portfolio. This product is unsurpassed worldwide due to the main principle being based on tool-free installation. The product is used in those areas where a threaded bolt on the load is used instead of a simple thread. Furthermore, there is a possibility to mount the lifting point PLGW-SN with a commercially available (standard) screw through the clearance hole. The benefit of the PLGW-SN is that no matter the width of the load, the same lifting point can be used – all one needs are standard screws with different screw lengths.

For more details, please refer to the instruction manual.

Further benefits of the PLGW-SN lifting points supreme are:

- Tools are not necessary for assembling or disassembling
- The time saving aspect especially when frequent
- (dis)assembling takes placeRotatable (load direction adjustment)
- In all directions loadable

Applicaton 1: Employement PLGW or PLGW-SN

Picture 1

NEW!

Picture 2

Picture 3

Application 2: Differing load thickness/width

Application 3: Available Threaded Bolts

Type of application Number of legs Angle of inclination		6 1 0°	لو 1 90°	¢ 6 2 0°	ل <mark>ا ہے۔</mark> 2 90°	2 0°-45°	2 45°-60°	3+4 0°-45°	3+4 45°-60°	2 unsymm.	3+4 unsymm.
Code	Thread [mm]	Load capa [kg]	acity								
PLGW-SN 0,7 t	M12	2.000	700	4.000	1.400	1.000	700	1.400	1.000	700	700

PLGW-SN 1,5 t	M16	4.000	1.500	8.000	3.000	2.100	1.500	3.000	2.200	1.500	1.500
PLGW-SN 2,3 t	M20	4.500	2.300	9.000	4.600	3.200	2.300	4.800	3.400	2.300	2.300
PLGW-SN 3,5 t	M24	5.000	3.500	10.000	7.000	4.900	3.500	7.400	5.200	3.500	3.500

Code	Thread [mm]	Load capacity [kg]	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	Ø f [mm]	() [mm]	Weight [kg/pc.]
PLGW-SN 0,7 t	M12	700	30	55	12	25	65	43	14	0,28
PLGW-SN 1,5 t	M16	1.500	35	64	14	29	72	50	19	0,42
PLGW-SN 2,3 t	M20	2.300	40	69	16	34	80	54	22	0,50
PLGW-SN 3,5 t	M24	3.500	50	86	18	40	95	69	27	1,00

Comparison between PLGW/PLGW-SN pewag profilift gamma and eyebolt DIN 580

Why should I use PLGW pewag profilift gamma?

PLGW pewag profilift gan PLGW-SN pewag profilift	nma supreme eyebolt resp. gamma supreme eye nut		Eye bol Eye bol	according to DIN according to DIN	I 580 resp. I 582		
				0			
	Product	PLGW (SN)	DIN 580 / DIN	582	PLGW (SN)	DIN 580 / DIN 5	582
	Thread size	M12	M12	1*) 2*)	M36	M36	1*) 2*)
	Nominal load capacity	0,7 t	0,34 t		7 t	4,6 t	
(\bigcirc)	Working load limit WLL	2 t	0,34 t	M30	15 t	4,6 t	M64
	Breaking load limit	8 t	2,04 t		60 t	27,6 t	
5450	WLL (< 45°)	0,7 t	0,24 t	M20	7 t	3,3 t	M56
	Breaking load limit (< 45°)	2,8 t	1,44 t		28 t	19,8 t	
545° 545°	WLL (< 45° side loaded)	0,7 t	0,17 t	M24	7 t	2,3 t	M64
	Breaking load limit (< 45° side loaded)	2,8 t	1,02 t		28 t	13,8 t	

- 1*) What size DIN 580 is needed to carry the same load as the pewag profilift gamma (in the appropriate direction of loading).
- Application: Single-sling, direct load, Load = 2 t. Required thread size pewag PLGW: M12 Required thread size eye bolt acc. to DIN 580: M30

Application: Multi leg sling

2*) The carrying capacity of DIN 580 shall apply only if the screws are screwed in completely and rest on the load with the entire contact surface. Since it is very likely in this case, that at least one screw is loaded in the wrong direction, pewag recommends the adjustable eye bolts PLGW.
Those can always be aligned in the tensile direction.

Size comparison PLGW M12 - DIN 580-M30

Screwable lifting points dlhonline.co.uk 0161 223 1990

PLAW pewag winner profilift alpha

360° rotatable lifting point. The load ring is loadable in a range of 130° and can be positioned at any required angle due to its replaceable and patented spring. Likewise interchangeable is the hexagon-special screw from grade 10.9 material, which is sesecured against loss. The screw is 100% crack detection tested as well as covered with a chromate VI-free protection against corrosion, and marked with the load capacity and thread size.

pewag winner profilift alpha is able to withstand a 4-fold safety against break in all directions. Each lifting point is marked with an individual serial number that allows product traceability. pewag winner profilift alpha is available with metric or UNC-thread, whereas the lifting points with metric thread are also obtainable with customized thread lengths. The table with the working load limit depending on the type of application as lifting gear, number of legs and angle of inclination is a part of the user manual and packed together with each lifting point.

PLAW 0,3 - 1,5

PLAW 2,5 - 20

Picture 1: permissible usage

Method of lifting		G							÷	
Number of legs	1	1	2	2	2	2	3+4	3+4	2	3+4
Angle of inclination	0 °	90°	0 °	90°	0°–45°	45°–60°	0°–45°	45°–60°	asymm.	asymm.

Code	Thread	Fastening torque	Load cap	acity								
	[mm]	[Nm]	[kg]									
PLAW 0,3 t	M8	35	300	300	600	600	400	300	600	400	300	300
PLAW 0,63 t	M10	70	630	630	1.250	1.250	850	630	1.300	900	630	630
PLAW 1 t	M12	120	1.000	1.000	2.000	2.000	1.400	1.000	2.100	1.500	1.000	1.000
PLAW 1,5 t	M16	200	1.500	1.500	3.000	3.000	2.100	1.500	3.100	2.200	1.500	1.500
PLAW 2,5 t	M20	250	2.500	2.500	5.000	5.000	3.500	2.500	5.200	3.700	2.500	2.500
PLAW 4 t	M24	400	4.000	4.000	8.000	8.000	5.600	4.000	8.400	6.000	4.000	4.000
PLAW 6 t	M30	500	6.000	6.000	12.000	12.000	8.500	6.000	12.650	9.000	6.000	6.000
PLAW 7 t*	M36	700	7.000	7.000	14.000	14.000	9.800	7.000	14.700	10.500	7.000	7.000
PLAW 8 t	M36	800	8.000	8.000	16.000	16.000	11.200	8.000	16.800	12.000	8.000	8.000
PLAW 10 t	M42	1.000	10.000	10.000	20.000	20.000	14.000	10.000	21.000	15.000	10.000	10.000
PLAW 15 t	M42	1.500	15.000	15.000	30.000	30.000	21.000	15.000	31.500	22.500	15.000	15.000
PLAW 20 t	M48	2.000	20.000	20.000	40.000	40.000	28.000	20.000	42.000	30.000	20.000	20.000

Code	Thread	Fastening torque	Load capa	acity								
	[inch]	[Ib/ft]	[Ibs]									
PLAW U 3/8	3/8"-16	51,6	1.350	1.350	2.700	2.700	1.800	1.350	2.800	1.900	1.350	1.350
PLAW U 1/2	1/2"-13	88,5	2.200	2.200	4.400	4.400	3.000	2.200	4.600	3.300	2.200	2.200
PLAW U 5/8	5/8"-11	148	3.300	3.300	6.600	6.600	4.600	3.300	6.800	4.800	3.300	3.300
PLAW U 3/4	3/4"-10	221	4.400	4.400	8.800	8.800	6.000	4.400	9.200	6.500	4.400	4.400
PLAW U1	1"-8	295	8.800	8.800	17.600	17.600	12.300	8.800	18.400	13.200	8.800	8.800
PLAW U1 1/4	1 1/4"-7	369	13.200	13.200	26.400	26.400	18.700	13.200	27.800	19.800	13.200	13.200
PLAW U1 1/2	1 1/2"-6	590	17.000	17.000	34.000	34.000	24.000	17.000	36.000	25.500	17.000	17.000
PLAW U1 3/4	1 3/4"-5	1.100	22.000	22.000	44.000	44.000	30.000	22.000	45.000	33.000	22.000	22.000

* Special models only available on request!

Safety factor 4

dlhonline.co.uk 0161 223 1990 pewag

Permissible usage

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull (see picture 1).

Non permissible usage

Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area (see picture 2)
- Load ring rests against edges or load (picture 3)

The load ring must be placed in the direction of pull before loading – do not turn under load. For more details please have a look into our user manual.

To calculate the necessary thread length (L):

L=H+S+K+X

H = Material height

S = Thickness of the washer

 $\mathsf{K}=\mathsf{Height}$ of the nut (depending on the thread size of the screw)

 $X=\mbox{Excess}$ length of the screw (twofold pitch of the screw)

 $L \max = n \max$.

pewag provides, along with the standard and maximum thread lengths, specially customised thread lengths.

Supplied customised and maxium thread lengths include a washer and a crack-tested, corrosion-proofed screw nut.

Picture 2

Picture 3

Code	Thread	Load capacity	9	h	c	d	0	a	h	k	n	n may	\bigcirc	<u> </u>	Weight
Code	[mm]	[kg]	[mm]	[mm]	[mm]	[mm]	[mm]	9 [mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/pc.]
PLAW 0,3 t	M8	300	45	67	40	11	41	95	23	55	20	150	6	-	0,57
PLAW 0,63 t	M10	630	45	67	40	11	41	95	23	55	20	150	8	-	0,58
PLAW 1 t	M12	1.000	45	67	40	11	41	95	23	55	33	170	10	24	0,60
PLAW 1,5 t	M16	1.500	45	67	40	11	41	95	23	55	33	260	10	24	0,62
PLAW 2,5 t	M20	2.500	54	81	50	13	55	112	33	67	33	335	8	24	1,10
PLAW 4 t	M24	4.000	75	115	67	20	68	143	45	100	36	364	19	-	3,00
PLAW 6 t	M30	6.000	75	115	67	20	68	143	45	100	49	364	14	36	3,10
PLAW 7 t *	M36	7.000	75	115	67	20	65	143	45	100	55	-	27	-	3,30
PLAW 8 t	M36	8.000	93	147	85	27	85	188	52	120	55	365	19	36	6,10
PLAW 10 t	M42	10.000	93	147	85	27	85	188	52	120	65	365	32	-	6,40
PLAW 15 t	M42	15.000	115	181	105	33	108	246	63	150	63	340	19	55	12,0
PLAW 20 t	M48	20.000	115	181	105	33	108	246	63	150	73	340	19	55	12,3
Code	Thread [inch]	Load capacity [lbs]	a [inch]	b [inch]	c [inch]	d [inch]	e [inch]	g [inch]	h [inch]	k [inch]	n [inch]	n max. [inch]	(inch]	⊑℃ [inch]	Weight [lbs/pc.]
PLAW U 3/8	3/8"-16	1.350	1,77	2,64	1,57	0,43	1,61	3,74	0,91	2,17	0,79	-	5/16"	-	1,39
PLAW U 1/2	1/2"-13	2.200	1,77	2,64	1,57	0,43	1,61	3,74	0,91	2,17	1,30	-	3/8"	-	1,41
PLAW U 5/8	5/8"-11	3.300	1,77	2,64	1,57	0,43	1,61	3,74	0,91	2,17	1,30	-	1/2"	-	1,45
PLAW U 3/4	3/4"-10	4.400	2,13	3,19	1,97	0,51	2,17	4,41	1,34	2,64	1,30	-	9/16"	-	2,36
PLAW U1	1"-8	8.800	2,95	4,53	2,64	0,79	2,68	5,63	1,77	3,94	1,41	-	3/4"	-	6,40
PLAW U1 1/4	1 1/4"-7	13.200	2,95	4,53	2,64	0,79	2,68	5,63	1,77	3,94	1,93	-	7/8"	-	6,80
PLAW U1 1/2	1 1/2"-6	17.000	3,66	5,79	3,35	1,06	3,43	7,40	2,05	4,72	2,16	-	1"	-	14,40
PLAW U1 3/4	1 3/4"-5	22.000	3,66	5,79	3,35	1,06	3,43	7,40	2,05	4,72	2,55	-	1 1/4"	-	14,70

* Special models only available on request!

Screwable lifting points

dlhonline.co.uk 0161 223 1990

PLBW pewag winner profilift beta

360° rotatable lifting point. The load ring is 180° movable and can be positioned at any required angle due to its replaceable and patented spring. Likewise interchangeable is the hexagon-special screw of grade 10.9 material, which is secured against loss. The screw is 100% crack-tested as well as covered with a chromate VI-free protection against corrosion, and marked with WLL and thread size. It can be tightened with a hexagon wrench or spanner wrench.

The lifting points pewag winner profilift beta are marked with an individual serial number, that allows product traceability and load capacity for the most inappropriate field of operation, which explains the increased WLL in the upright loaded position. In permissible fields of operations the lifting point corresponds to a 5-fold safety. pewag winner profilift beta is available with metric or UNC-thread, whereas the lifting points with metric thread are also obtainable with customized thread lengths. The table with the different load capacities depending on the method of lifting as lifting gear, number of legs and angle of inclination is a part of the user manual and packed together with each lifting point.

Picture 1

Picture 2

		ŧ	<u>t t</u> ,	i i	5%	7 %			\sim	
Method of lifting	6	Ģ	Ģ	L C L	G	ß			G	
Number of legs	1	1	2	2	2	2	3+4	3+4	2	3+4
Angle of inclination	0 °	90°	0 °	90°	0°–45°	45°–60°	0°–45°	45°–60°	asymm.	asymm.

Code	Thread [mm]	Fastening torque [Nm]	Load capa [kg]	acity								
PLBW 0,3 t	M8	6	500	300	1.000	600	400	300	600	450	300	300
PLBW 0,6 t	M10	10	1.000	600	2.000	1.200	800	600	1.300	900	600	600
PLBW 1 t	M12	15	1.300	1.000	2.600	2.000	1.400	1.000	2.100	1.500	1.000	1.000
PLBW 1,3 t	M14	30	2.000	1.300	4.000	2.600	1.800	1.300	2.700	1.900	1.300	1.300
PLBW 1,6 t	M16	50	2.500	1.600	5.000	3.200	2.200	1.600	3.400	2.400	1.600	1.600
PLBW 2 t	M18	70	3.000	2.000	6.000	4.000	2.800	2.000	4.200	3.000	2.000	2.000
PLBW 2,5 t	M20	100	3.500	2.500	7.000	5.000	3.500	2.500	5.300	3.700	2.500	2.500
PLBW 3 t	M22	120	4.500	3.000	9.000	6.000	4.200	3.000	6.300	4.500	3.000	3.000
PLBW 4 t	M24	160	5.500	4.000	11.000	8.000	5.600	4.000	8.400	6.000	4.000	4.000
PLBW 5 t	M27	200	6.500	5.000	13.000	10.000	7.000	5.000	10.500	7.500	5.000	5.000
PLBW 6,3 t	M30	250	7.000	6.300	14.000	12.600	8.800	6.300	13.200	9.400	6.300	6.300
PLBW 8 t	M33	270	9.000	8.000	18.000	16.000	11.000	8.000	16.500	12.000	8.000	8.000
PLBW 10 t	M36	320	11.000	10.000	22.000	20.000	14.000	10.000	21.000	15.000	10.000	10.000
PLBW 12,5 t	M42	400	13.500	12.500	27.000	25.000	17.500	12.500	26.300	18.700	12.500	12.500
PLBW 15 t	M48	600	16.000	15.000	32.000	30.000	21.000	15.000	32.000	22.500	15.000	15.000

Code	Thread [inch]	Fastening torque [lb/ft]	Load cap [lbs]	acity								
PLBW U5/16	5/16"-18	4,5	1.100	660	2.200	1.320	900	660	1.400	900	660	660
PLBW U 3/8	3/8"-16	7,5	2.200	1.300	4.400	2.600	1.800	1.300	2.700	1.900	1.300	1.300
PLBW U 7/16	7/16"-14	11	2.800	2.200	5.600	4.400	3.000	2.200	4.600	3.300	2.200	2.200
PLBW U 9/16	9/16"-12	22	4.400	3.000	8.800	6.000	4.200	3.000	6.300	4.500	3.000	3.000
PLBW U 5/8	5/8"-11	37	5.500	3.500	11.000	7.000	4.900	3.500	7.300	5.200	3.500	3.500
PLBW U 3/4	3/4"-10	74	6.600	5.500	13.200	11.000	7.700	5.500	11.500	8.200	5.500	5.500
PLBW U 7/8	7/8"-9	118	12.000	8.800	24.000	17.600	12.300	8.800	18.500	13.200	8.800	8.800
PLBW U1	1"-8	148	13.000	11.000	26.000	22.000	15.400	11.000	23.000	16.500	11.000	11.000
PLBW U1 1/8	1 1/8"-7	185	14.300	13.500	28.600	27.000	18.900	13.500	28.300	20.200	13.500	13.500
PLBW U1 1/4	1 1/4"-7	200	19.800	17.500	39.600	35.000	24.500	17.500	36.700	26.200	17.500	17.500
PLBW U1 3/8	1 3/8"-6	236	24.000	22.000	48.000	44.000	30.800	22.000	46.200	33.000	22.000	22.000
PLBW U1 1/2	1 1/2"-6	295	25.000	24.000	50.000	48.000	33.600	24.000	50.400	36.000	24.000	24.000

Safety factor 5

dlhonline.co.uk 0161 223 1990 pewag

Permissible usage

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull (see picture 1 and 2).

Non permissible usage

Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area (see picture 3)
- Loading ring rests against edges or load (picture 4)

The load ring must be placed in the direction of pull before loading – do not turn under load. For more details please have a look into our user manual.

To calculate the necessary thread length (L):

L=H+S+K+X

H = Material height

S = Thickness of the washer

K = Height of the nut (depending on the thread size of the screw)

X = Excess length of the screw (twofold pitch of the screw)

L max. = n max.

pewag provides, along with the standard and maximum thread lengths, specially customised thread lengths.

Supplied customised and maxium thread lengths include a washer and a crack-tested, corrosion-proofed screw nut.

Picture 3

Picture 4

Code	Thread [mm]	Load capacity [kg]	a [mm]	b [mm]	c [mm]	e [mm]	f [mm]	g [mm]	h [mm]	n [mm]	n max. [mm]	(mm]	⊏℃ [mm]	Weight [kg/pc.]
PLBW 0,3 t	M8	300	29	56	30	38	18	27	94	13	80	8	15	0,32
PLBW 0,6 t	M10	600	29	56	30	38	18	27	94	15	100	8	15	0,33
PLBW 1 t	M12	1.000	29	56	30	38	18	27	94	17	180	8	15	0,34
PLBW 1,3 t	M14	1.300	43	79	45	55	25	38	138	22	220	10	24	1,03
PLBW 1,6 t	M16	1.600	43	79	45	55	25	38	138	24	260	10	24	1,04
PLBW 2 t	M18	2.000	43	79	45	55	25	38	138	27	295	10	24	1,07
PLBW 2,5 t	M20	2.500	43	79	45	55	25	38	138	30	335	10	24	1,08
PLBW 3 t	M22	3.000	64	118	68	85	38	58	209	33	355	14	36	3,50
PLBW 4 t	M24	4.000	64	118	68	85	38	58	209	36	355	14	36	3,53
PLBW 5 t	M27	5.000	64	118	68	85	38	58	209	40	355	14	36	3,58
PLBW 6,3 t	M30	6.300	64	118	68	85	38	58	209	45	355	14	36	3,66
PLBW 8 t	M33	8.000	106	188	108	132	60	91	331	54	328	19	55	14,50
PLBW 10 t	M36	10.000	106	188	108	132	60	91	331	59	328	19	55	14,60
PLBW 12,5 t	M42	12.500	106	188	108	132	60	91	331	69	328	19	55	14,90
PLBW 15 t	M48	15.000	106	188	108	132	60	91	331	74	328	19	55	15,20
Code	Thread [inch]	Load capacity [lbs]	a [inch]	b [inch]	c [inch]	e [inch]	f [inch]	g [inch]	h [inch]	n [inch]	n max. [inch]	(inch]	⊏℃ [inch]	Weight [lbs/pc.]
PLBW U5/16	5/16"-18	660	1,14	2,20	1,18	1,50	0,71	1,06	3,70	0,51	-	5/16"	5/8"	0,71
PLBW U3/8	3/8"-16	1.300	1,14	2,20	1,18	1,50	0,71	1,06	3,70	0,59	-	5/16"	5/8"	0,73
PLBW U7/16	7/16"-14	2.200	1,14	2,20	1,18	1,50	0,71	1,06	3,70	0,67	-	5/16"	5/8"	0,75
PLBW U9/16	9/16"-12	3.000	1,69	3,11	1,77	2,17	0,98	1,50	5,43	0,87	-	5/16"	1"	2,27
PLBW U5/8	5/8"-11	3.500	1,69	3,11	1,77	2,17	0,98	1,50	5,43	0,95	-	5/16"	1"	2,29
PLBW U3/4	3/4"-10	5.500	1,69	3,11	1,77	2,17	0,98	1,50	5,43	1,19	-	5/16"	1"	2,38
PLBW U7/8	7/8"-9	8.800	2,52	4,65	2,68	3,35	1,50	2,28	8,23	1,44	-	9/16"	1 3/8"	7,78
PLBW U1	1"-8	11.000	2,52	4,65	2,68	3,35	1,50	2,28	8,23	1,59	-	9/16"	1 3/8"	7,89
PLBW U1 1/8	1 1/8"-7	13.500	2,52	4,65	2,68	3,35	1,50	2,28	8,23	1,79	-	9/16"	1 3/8"	8,07
PLBW U1 1/4	1 1/4"-7	17.500	4,17	7,40	4,25	5,20	2,36	3,58	13,03	2,13	-	3/4"	2 3/16"	32,00
PLBW U1 3/8	1 3/8"-6	22.000	4,17	7,40	4,25	5,20	2,36	3,58	13,03	2,32	-	3/4"	2 3/16"	32,20
PLBW U1 1/2	1 1/2"-6	24 000	4 17	7.40	4 25	5 20	2.36	3 58	13.03	2.72	-	3/4"	2 3/16"	32 80

Screwable lifting points

dlhonline.co.uk 0161 223 1990

PLDW pewag winner profilift delta

Ball-bearing 360° under load rotatable lifting point. High resistant lifting eye 180° movable. The special screws are 100% crack-tested as well as protected against corrosion, and marked with WLL and thread size. Each lifting point is marked with an individual serial number, that allows traceability. The table with the load capacities depending on the method of lifting as lifting gear, number of legs and angle of inclination is a part of the user manual and packed together with each lifting point.

The pewag winner profilift delta lifting points are marked with a WLL for the most inappropriate field of application, which explains the increased WLL in the upright loaded position, with a 4-fold safety against break in all directions of load.

Method of lifting		t o d		ار م با				Þ	r t t	
Number of legs	1	1	2	2	2	2	3+4	3+4	2	3+4
Angle of inclination	0°	90°	0°	90°	0°–45°	45°–60°	0°–45°	45°–60°	asymm.	asymm.

Code	Thread	Fastening torque	Load capa	acity								
	[mm]	[Nm]	[kg]									
PLDW 0,3 t	M8	10	600	300	1.200	600	400	300	600	400	300	300
PLDW 0,5 t	M10	10	1.000	500	2.000	1.000	700	500	1.000	750	500	500
PLDW 0,7 t	M12	15	1.400	700	2.800	1.400	950	700	1.400	1.000	700	700
PLDW 1 t*	M14	25	2.000	1.000	4.000	2.000	1.400	1.000	2.100	1.500	1.000	1.000
PLDW 1,5 t	M16	30	2.600	1.500	5.200	3.000	2.100	1.500	3.100	2.100	1.500	1.500
PLDW 2,5 t	M20	80	4.500	2.500	9.000	5.000	3.500	2.500	5.300	3.500	2.500	2.500
PLDW 4 t	M24	150	7.000	4.000	14.000	8.000	5.500	4.000	8.400	6.000	4.000	4.000
PLDW 6 t	M30	230	10.000	6.000	20.000	12.000	8.400	6.000	12.600	9.000	6.000	6.000
PLDW 8 t	M36	450	12.500	8.000	25.000	16.000	11.200	8.000	16.800	12.000	8.000	8.000
PLDW 10 t	M42	600	16.000	10.000	32.000	20.000	14.000	10.000	21.000	15.000	10.000	10.000
PLDW 12,5 t	M48	600	16.000	12.500	32.000	25.000	17.500	12.500	26.200	18.000	12.500	12.500

* Special models only available on request!

pewag winner profilift lifting points

Safety factor 4

Availability on request!

dlhonline.co.uk 0161 223 1990 pewag

Permissible usage

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull (see picture 1).

Non permissible usage

Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area (see picture 2)
- · Loading ring rests against edges or load

For more details please have a look into our detailed user manual.

Picture 1

Picture 2

Code	Thread [mm]	Load capacity [kg]	a [mm]	b [mm]	c [mm]	Ø d [mm]	Øe [mm]	n [mm]	⊏ € [mm]	Weight [kg/pc.]
PLDW 0,3t	M8	300	30	38	54	13	38	20	34	0,47
PLDW 0,5t	M10	500	30	38	54	13	38	20	34	0,47
PLDW 0,7t	M12	700	35	48	54	13	38	22	34	0,47
PLDW 1t *	M14	1.000	35	48	54	13	38	22	34	0,47
PLDW 1,5t	M16	1.500	35	48	54	13	38	33	34	0,49
PLDW 2,5t	M20	2.500	35	55	75	16	55	33	46	1,10
PLDW 4t	M24	4.000	40	66	82	17	63	40	50	1,50
PLDW 6t	M30	6.000	50	70	92	23	72	40	60	2,50
PLDW 8t	M36	8.000	50	91	124	23	92	55	75	4,30
PLDW 10t	M42	10.000	65	91	124	27	92	60	75	5,10
PLDW 12,5t	M48	12.500	65	116	124	27	92	68	75	5,40

* Only on request!

Availability on request!

AOR Lashing point

For mounting machine parts or vehicle bodies. Ideal for hanging of lifting and lashing gear.

Permissible usage

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull.

Non permissible usage

Make sure when choosing the assembly that improper charge can not arise e.g. if:

- The direction of pull is obstructed
- · Direction of pull is not in the foreseen area
- Loading ring rests against edges or loads

		ŧ	5 5	i i	5%	5%~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~			\sim	
Method of lifting	6	G	Ģ	ᄕᅙᆘ	G	ß			6	
Number of legs	1	1	2	2	2	2	3+4	3+4	2	3+4
Angle of inclination	0 °	90 °	0 °	90°	0°–45°	45°–60°	0°–45°	45°–60°	asymm.	asymm.

Code	Thread [mm]	Fastening torque [Nm]	Load cap [kg]	acity								
AOR 10	M16	170	3.150	3.150	6.300	6.300	4.250	3.150	6.700	4.750	3.150	3.150
AOR 13	M20	350	5.300	5.300	10.600	10.600	7.500	5.300	11.200	8.000	5.300	5.300
AOR 16	M30	950	8.000	8.000	16.000	16.000	11.200	8.000	17.000	11.800	8.000	8.000
AOR 22	M36	1900	15.000	15.000	30.000	30.000	21.200	15.000	31.500	22.400	15.000	15.000
AOR 26*	M42	2100	21.200	21.200	42.400	42.400	30.000	21.200	45.000	31.500	21.200	21.200
AOR 28*	M45	2400	25.000	25.000	50.000	50.000	33.500	25.000	50.000	37.500	25.000	25.000
AOR 32*	M56	3200	31.500	31.500	63.000	63.000	45.000	31.500	67.000	47.500	31.500	31.500
AOR 34*	M56	3200	36.000	36.000	72.000	72.000	50.000	36.000	75.000	53.000	36.000	36.000
* No stock item	1									Attention: S	ubject to tech	nical changes!

Grade 8

, atomioni cubject to teeninear enangeer

Code	Thread [mm]	Load capacity [kg]	for chain Ø	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	f [mm]	l [mm]	Weight [kg/pc.]
AOR 10	M16	3.150	10	90	40	38	18	112	57	130	1,54
AOR 13	M20	5.300	13	115	50	48	22	149	79	165	2,83
AOR 16	M30	8.000	16	150	65	62	26	183	93	212	5,87
AOR 22	M36	15.000	22	175	75	72	36	226	114	255	11,20
AOR 26	M42	21.200	26	200	95	90	45	272	142	295	19,30
AOR 28	M45	25.000	28	200	95	90	45	272	142	295	20,20
AOR 32	M56	31.500	32	230	110	100	48	336	193	330	31,70
AOR 34	M56	36.000	34	230	110	100	48	336	193	330	31,70

dlhonline.co.uk 0161 223 1990 pewag

RGS Alloy steel eyebolt

The high-tensile eyebolt RGS is usable for lifting of machine parts. Eyebolts may only be tightened manually. Not suitable for diagonal pull.

Permissible usage.

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull (see picture 1).

Non permissible usage

Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area (see picture 2 and 3)

Picture 2

Picture 3

Picture 1

Method of lifting			G	لرا	↓×↓ ⊡				÷	
Number of legs	1	2	1	2	2	2	3+4	3+4	2	3+4
Angle of inclination	0 °	0 °	90°	90°	0°–45°	45°–60°	0°–45°	45°–60°	asymm.	asymm.

Code	Thread [mm]	Load cap [kg]	acity	
RGS 8	M8	400	800	
RGS 10	M10	700	1.400	
RGS 12	M12	1.000	2.000	Please load the eyebolts RGS only in the vertical direction of pull!
RGS 14	M14	1.200	2.400	For those methods of lifting please use the screwable eyebolts
RGS 16	M16	1.500	3.000	PLGW or screwable lifting points PLAW, PLBW or PLDW.
RGS 20	M20	2.500	5.000	
RGS 24	M24	4.000	8.000	
Safety factor	4			Attention: Subject to technical changes

Code	Thread	Load capacity	а	b	с	d	Weight
	[mm]	[kg]	[mm]	[mm]	[mm]	[mm]	[kg/pc.]
RGS 8	M8	400	34	7	20	24	0,05
RGS 10	M10	700	38	8	22	30	0,10
RGS 12	M12	1.000	47	10	26	36	0,20
RGS 14	M14	1.200	57	14	29	40	0,30
RGS 16	M16	1.500	65	15	35	55	0,40
RGS 20	M20	2.500	73	17	39	59	0,60
RGS 24	M24	4.000	95	20	54	84	1,20

Other sizes available on request!

Content

Weldable lifting points	
Advantages	30
PLE pewag profilift eta	31

Weldable lifting points

Product Overview

Reliable. Innovative. pewag.

Latest technology for the heaviest duties

The weldable high quality manufactured pewag profilift lifting point is the ideal complement to the pewag winner lifting chain programme and expands their field of operations. The weldable pewag profilift lifting point guarantees an easy assembly and usage.

The weldable lifting point PLE is manufactured according to EG-Machine Directive 2006/42/EG and tested according to EN 1677-1. The load capacity is clearly marked on the welding pad.

The table with the load capacities depending on the different methods of lifting as lifting gear, number of legs and angle of inclination is a part of the user manual, which is packed together with each lifting point according to the Machine-Safety prescriptions 2010 and Machine-Directive.

Stamping PLE

User manual

DGUV Test certified

pewag

PLE pewag profilift eta

High-tensile eyebolts pewag profilift eta, for welding onto machine parts or vehicle bodies. Ideal for hanging of lifting and lashing parts. Due to the integrated spring, the ring will be kept in each requested position.

The instructions according to DIN EN ISO 14341 are valid for the welding. The welding may only be carried out by a welding operator with a valid qualification according to EN 287-1.

The lifting points will be packed individually and together with a user manual and welding instructions.

Permissible usage

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull - see picture 1 and 2.

Non permissible usage

Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area
- · Loading ring rests against edges and load

Picture 2

	4		5 5		the	Jet o	rat_		~	
Method of lifting	Ĝ	G	G	i _G i	G	G			[6]	
Number of legs	1	1	2	2	2	2	3+4	3+4	2	3+4
Angle of inclination	0 °	90°	0 °	90 °	0°–45°	45°–60°	0°–45°	45°–60°	asymm.	asymm.

Code	Load capacity	Load cap	acity								
	[kg]	[kg]									
PLE/N 6	1.120	1.120	1.120	2.240	2.240	1.500	1.120	2.300	1.600	1.120	1.120
PLE/N 8	2.000	2.000	2.000	4.000	4.000	2.800	2.000	4.200	3.000	2.000	2.000
PLE/N 10	3.150	3.150	3.150	6.300	6.300	4.400	3.150	6.600	4.700	3.150	3.150
PLE/N 13	5.300	5.300	5.300	10.600	10.600	7.400	5.300	11.200	7.900	5.300	5.300
PLE/N 16	8.000	8.000	8.000	16.000	16.000	11.300	8.000	16.900	12.000	8.000	8.000
PLE/N 22	15.000	15.000	15.000	30.000	30.000	21.000	15.000	31.800	22.500	15.000	15.000
Safety factor 4									Attontion: S	ubject to tech	nical changes

Safety factor 4

Attention: Subject to technical changes

Code	Load capacity	а	b	d	е	f	I	Weight
	[kg]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg/pc.]
PLE/N 6	1.120	36	40	11	67	42	35	0,28
PLE/N 8	2.000	37	42	13	73	45	37	0,39
PLE/N 10	3.150	41	45	16,50	80	47	40	0,62
PLE/N 13	5.300	61	55	22	97	53	50	1,40
PLE/N 16	8.000	63	70	25	120	73	64	2,30
PLE/N 22	15.000	89	97	33	163	92	90	5,50

32

Content

Spare partsPLMS Screw nut according to DIN 980 V34(set includes washer)34PLGS Screw for PLGW34PLGES Spare-Latches34PLAS Screw for PLAW35PLBS Screw for PLBW35Thread adapter for lifting points35

Spare parts

Product Overview

PLMS Screw nut according to DIN 980 V (set includes washer)

Spare parts for pewag winner lifting points with special length. The nuts are crack tested and have a strength class of at least 10 (DIN EN ISO 898). Set inludes nut and washer. Both have to be used together.

PLMS Screw nut according to DIN 980 V (set includes washer)	Code	Thread [mm]	SW [mm]	h [mm]	h1 [mm]	VPE [piece]
sw	PLMS 8	M8	13	8	1,6	10
	PLMS 10	M10	17	10	2	10
	PLMS 12	M12	19	12	2,5	10
	PLMS 16	M16	24	16	4	10
	PLMS 20	M20	30	20	4	10
In I	PLMS 24	M24	36	24	4	10
	PLMS 30	M30	46	30	5	4
	PLMS 36	M36	55	36	6	1
	PLMS 42	M42	65	42	7	1
	PLMS 48	M48	75	48	8	1

PLGS Screw for PLGW

Spare parts for PLGW pewag winner profilift gamma supreme with metric thread.

	Code	Thread	VPE
PLGS Screw for PLGW		[mm]	[piece]
	PLGS 0,3 t	M8	10
	PLGS 0,5 t	M10	10
	PLGS 0,7 t	M12	10
	PLGS 1,5 t	M16	10
	PLGS 2 t	M20	10
	PLGS 3 t	M24	10
	PLGS 4 t	M30	4
	PLGS 7 t	M36	1
	PLGS 9 t	M42	1
	PLGS 12 t	M48	1

PLGES Spare Latches

Spare latches for PLGW pewag winner profilift gamma supreme.

PLGES Spare Latches	Code	Thread [mm]	VPE [piece]
	PLGES 0,3 t	M8	1
	PLGES 0,5 t	M10	1
	PLGES 0,7 t	M12	1
	PLGES 1,5 t	M16	1
	PLGES 2 t	M20	1
	PLGES 3 t	M24	1
	PLGES 4 t	M30	1
	PLGES 7 t	M36	1
	PLGES 9 t	M42	1
	PLGES 12 t	M48	1

PLAS Screw for PLAW

Spare parts for PLAW pewag winner profilift alpha with metric thread. Only for type PLAW with sleeve.

PLAS Screw for PLAW	Code	Thread [mm]	VPE [piece]
	PLAS 0,3 t	M8	10
	PLAS 0,63 t	M10	10
	PLAS 1 t	M12	10
	PLAS 1,5 t	M16	10
	PLAS 2,5 t	M20	10
	PLAS 4 t	M24	10
	PLAS 6 t	M30	4
	PLAS 8 t	M36	1
	PLAS 10 t	M42	1
	PLAS 15 t	M42	1
	PLAS 20 t	M48	1

PLBS Screw for PLBW

Spare parts for PLBW pewag winner profilift beta with metric thread.

PLBS Screw for PLBW	Code	Thread [mm]	VPE [piece]
	PLBS 0,3 t	M8	10
	PLBS 0,6 t	M10	10
	PLBS 1 t	M12	10
	PLBS 1,3 t	M14	10
	PLBS 1,6 t	M16	10
	PLBS 2 t	M18	10
	PLBS 2,5 t	M20	10
	PLBS 3 t	M22	10
	PLBS 4 t	M24	10
	PLBS 5 t	M27	4
	PLBS 6,3 t	M30	4
	PLBS 8 t	M33	2
	PLBS 10 t	M36	1
	PLBS 12,5 t	M42	1
	PLBS 15 t	M48	1

Thread adapter for lifting points

Often loads already have tapped holes for DIN-580 eye-bolts. By using pewag's thread adapter, the high-strength pewag lifting points (PLAW, PLBW, PLGW, PLDW) can replace the standard eye-bolts. The thread adapter can be mounted using a commercial open-jawed spanner; the pewag lifting point is then mounted according to the instruction manual. The permitted working load capacity corresponds to the screwed pewag lifting point fitted in the internal thread.

Available on request only!

User manual

36

38–39

User manual

User manual

dlhonline.co.uk 0161 223 1990

User manual

User manual for usage, storage, inspection and maintenance of pewag winner lifting points.

General

pewag winner profilift lifting points can be used for general lifting purposes in a wide range regarding the design, type of load and type of application. Regarding the details corresponding to the design and the classification of the WLL of the different types of applications, please have a look at the tables in this catalogue. pewag winner profilift lifting points offer the highest level of safety in case of ordinary usage. However, damage to property or persons can only be avoided through ordinary usage. Reading and understanding our user manual is thus a pre-condition for the usage of pewag winner profilift lifting points, but on the other hand it does not exclude the responsible and foresighted handling in case of all lifting procedures. Please follow the provided instruction before and during the assembly.

Change of the as-delivered condition

Please only use the provided original parts in the installation. The original condition may not be changed e.g. through grinding, welding (except lashing point PLE), stamping, drilling etc. pewag can not overtake any liability in case of usage of non original-parts. Any treatment of the surface like hot-dip galvanizing, galvanic galvanization etc. is forbidden. Canterizing and other cleaning methods are also dangerous processes and must be confirmed by pewag. The welding seam of the lifting points PLE can be protected against corrosion by painting.

Accurate usage

pewag winner profilift lifting points may only be used by assigned and trained persons. The location point of the load shall be set in the manner specified that the transmitted forces of the raw material can be absorbed without any deformations. The load bracket needs to be adjusted in the direction of pull before loading. You have to choose the location point in such a way that unpermissible stresses such as twisting or rotating of the load are avoided. Mounting and demounting of the lifting gear must be possible without any risk of injury. Damages of the load, lifting gear or lifting point need to be excluded by proper positioning. In case of usage of only 1 lifting point, it has to be mounted flat over the center of gravity of the load. When using 2 lifting points (2-leg chainsling), those have to be mounted symmetrically on both sides of the center of gravity of the load. When using 3 or 4 lifting points (3 or 4-leg chainslings), those have to be mounted permanently in one section around the center of gravity of the load.

Thereby you have to take care, that the load on the individual chain legs is located evenly. In case of asymmetrical load distribution, the load capacity has to be reduced according to the enclosed table of working load limits. Hence it can be possible that you have to choose a lifting point of the subsequent load capacity. Please do not subject the lifting points neither to acids or leaches nor to their steams. Attention: Certain manufacturing procedures set free acids respectively steams. If the lifting points are subject to higher temperatures, it will also reduce the load capacity. Therefore please pay attention to the provided instructions or get in contact with our technical service.

Screwable lifting points

As the minimum screw penetration we recommend:

- 1 x M for steel (M= thread size e.g. M16)
- 1.25 x M for casted steel
- 2 x M for aluminium

For materials of lower strength, like light metals, nonferrous metals or cast iron, the user has to choose the thread size and thread length in order that the load can be absorbed by it. Predictable impact stress or vibration can cause the accidental loss of the screw. As an assurance for such a case you can use e.g. liquid thread adhesive for example Loctite (pay attention to the manufacturer instruction). If using parts which were not delivered from pewag e.g. screws, we can not accept any liability!

Before each usage, please check the following points:

- Tightened screws fastening torque according to provided instruction
- Completeness of the lifting point
- · Full legibility of the stamping of the lifting point
- Damages such as grooves, cracks, deformations, wear, severe corrosion, cracks on loaded parts, visible marks of excessive heat treatment (e.g. burned finish or discoloration of the raw material), easy, free of hitches rotation of the turnable lifting points etc.

Furthermore please check before assembly:

- · Damage of the screws and thread
- · Correct screw size, screw grade and screw depth

It is imperative to pay attention to the provided instructions! In case of doubt respectively damages on the lifting points, please take it out of service and let it be inspected by a competent person. The same is valid for extraordinary occasions such as uncontrollable heat influence.

Weldable lifting points

The following instructions have to be considered in case of welding:

- The welding has to be done by a proof tested welder according to EN 287-1
- Material of the weld bracket: S355 J2 G3 (1.0570).
- The surface of the weld region must be cleaned thoroughly before starting the welding process. Cinder, colour, oil etc. must be removed
- Please exclude any contact between the coated ring and the filler metal

Before each application, please check the following points:

- · Full legibility of the stamping of the lifting point
- Damages such as grooves, cracks, deformations, wear, severe corrosion, cracks on loaded parts, visible marks of excessive heat treatment (e.g. burned finish or discoloration of the raw material), easy, free of hitches rotation of the turnable lifting points etc.
- · Cracks or damages on the weld seam

It is imperative to pay attention to the provided instructions! In case of doubt respectively damages on the lifting points, please take it out of service and let it be inspected by a competent person. The same is valid for extraordinary occasions such as uncontrollable heat influence.

Maintenance

The maintenance of pewag winner profilift lifting points may only be executed by a competent person.

Inspection

Every 12 months an inspection must be carried out according to the national standards by a competent person. In case of frequent full load, this period can also be shortened up. Records of the inspections, particularly their results as well as the maintenance are to be kept in safe custody during the whole service life of the lifting points.

Storage

pewag winner profilift lifting points have to be stored cleaned, dehumidified and protected against corrosion e.g. oiled. The thread shanks must be protected with suitable means against damages.

Attention

With the exception of the alloy steel eyebolt RGS, all pewag winner profilift lifting points can also be used as lashing points. Thus the permissible tensile force is the duplicate of the nominal load capacity, as in case of the tie-down the 2-fold safety is valid. With the lifting points PLBW a 2.5 fold safety is valid because of their safety factor of 5 in case of lifting. If you would like to use it as a lashing point, please get in contact with pewag.

Example

PLE 8 = 2.000 kg WLL in case of lifting. As lashing point LC = 4000 daN permissible tensile force (LC = Lashing capacity)

More precised details (WLL, dimensions, 3D-models) can be obtained under Chain systems/Lifting points from our website www.pewag.com. Each lifting points is packed together with a bilingual user manual.

Detailed user manual available for download on www.pewag.com

Dale Lifting and Handling Specialists 2 Kelbrook Road, Parkhouse Street Industrial Estate, Manchester, M11 2QA Telephone 0161 223 1990 Email sales@dale-lifting.co.uk www.dlhonline,co,uk

pewag austria GmbH A-8041 Graz, Gaslaternenweg 4, Phone: +43 316 6070-0, Fax: +43 316 6070-100, saleinfo@pewag.com, www.pewag.com

You Tube youtube.pewag.com

Promotion sustainable forest management

