



## Tiger Webbing Puller Model No. WS



### Main Features

- Capacities 1t and 1.5t
- When clean and dry the web strap is non-conductive
- Insulated handle
- Handle rotates full 360°
- Automatic brake with notch at a time operation
- Up-Neutral-Down
- Free wheeling
- Lightweight and compact
- Voltage Proof Test 15kV
- 4:1 factor of safety



# Tiger Lifting Products 0161 223 1990

Tiger Webbing Pullers are designed for use in hot line applications. They are lightweight and incorporate a webbing strap and lever handle. When clean and dry, the polyester webbing strap provides insulating properties. Along with the Fibre Reinforced Plastic (FRP) insulated handle this increases electrical safety when tensioning conductors and similar tasks. It also has a load holding function in both forward and reverse modes which are selected by a single click of the ratchet tab. The handle can rotate 360° to allow the most efficient use of the ratchet at any angle.

Not to be used for lifting. Not to be used for supporting people.

Each unit supplied with Manufacturer's Instructions for Use.

## Technical Data

Code	Capacity (tonne)	Strap Size (mm)	Lever Length (mm)	Max Length (mm)	Min Length (mm)	Weight (Kg)
WS-1000	1.0t	2 x 33	400	2000	420	3.2
WS-1500	1.5t	2.2 x 40	460	2000	420	4.5



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.

05 July 2017

**SGS**



Page 2 of 2

**DLH**ONLINE Division of Dale Group of Companies  
Dale Lifting and Handling Specialists  
2 Kelbrook Road Manchester M11 2QA  
Website [www.dlhonline.co.uk](http://www.dlhonline.co.uk) Email [sales@dale-lifting.co.uk](mailto:sales@dale-lifting.co.uk)